


Industrial Operator Panel With 4.3" touch screen Color graphic display OP MT line 0504TV line

- 4.3" color graphic display
- 256 colors TFT LCD display
- CPU 32 Bit RISC processor
- LED backlight
- 480 x 272 pixels resolution
- 4 wires analog resistive touch screen
- Connection to industrial bus systems (more than 65 drivers)
- 4 MB DRAM user memory, 2 MB flash memory on board
- NEMA4 / IP65 front panel protection
- Programmable with Easy Builder 500 software
- Display data in alphanumeric and graphic formats
- Dynamic graphic objects (bargraphs, gauges, XY plot, etc..)
- Data acquisition and trend presentation
- Alarms and historical alarm list
- Up to 7 levels of password protection
- CE certification



E

ISO 9001 Certified



ASCON Spa

Via Falzarego, 9/11
20021 Baranzate
Milano - ITALY
Tel. +39 02 333 371
Fax +39 02 350 4243
Web <http://www.ascon.it>
e-mail sales@ascon.it

ASCON Corporation

1884 East Fabyan Parkway
Batavia, Illinois 60510
UNITED STATES
Tel. +1 630 482 2950
Fax +1 630 482 2956
Web <http://www.asconcorp.com>
e-mail sales@asconcorp.com

ASCON France

2 bis, Rue Paul Henri Spaak
St. Thibault Des Vignes
F-77462 Lagny sur Marne - Cedex - FRANCE
Tel. +33 (0) 1 6430 6262
Fax +33 (0) 1 6430 8498
Web <http://www.ascon.fr>
e-mail ascon.france@ascon.fr

Technical data

Display	
Type	256 color TFT
Graphic resolution	480 x 272 pixels
Active display area	4.3" diagonal
Backlight	LED
Brightness	300 cd/m ²
Contrast ratio	400 : 1
Backlight life time	80,000 hours

Memory	
User memory	4 MB DRAM on board
Storage memory	2 MB flash on board
Expansion	None


Interfaces	
Com1 port	RS-232/RS-422/RS-485
Com2 port	None
Com3 port	None
Ethernet port	None
USB port	None
Audio port	None

Functionalities	
Data acquisition and trends	Standard
Recipes memory	None
Alarms	1024
Event list	1024
Password	Standard, 7 levels
Hardware RTC	None
Screen saver	Standard
Buzzer	Feedback for touch screen
Power supply	12 ~ 24 Vdc ± 5%
Max power consumption	~ 300 mA@ 12 Vdc ~ 150 mA@ 24 Vdc
Fuse	1 A
Weight	~ 0.3 Kg (0.66 lbs)
Operating temperature	0...45 °C (32...113 °F)
Operating and storage humidity	10..90% RH non condensing
Protection class	NEMA4 / IP65 (front panel)

Product designed for installation in an industrial environment in compliance with the following regulations:
 Radiation emissions complies with FCC class A
 Generic emissions EN 50081-2
 Noise immunity EN 50082-2

Connections/Dimensions

Connections



Cutout and front view

Panel dimension L x H	128 x 102 mm (5.04 x 4.02 in)
Cutout A x B	119 x 93 mm (4.69 x 3.66 in)
Cutout depth (type - 0045)	38 mm (1.50 in)

Pin #	Id	RS-422	RS-485	RS-232	PROG
1	RX -	RX -	DATA +		
2	RX +	RX +	DATA -		
3	TX -	TX -			
4	TX +	TX +			
5	GND	Signal Ground			
6	TX D			TX	
7	TX D				TX
8	RX D				RX
9	RX D			RX	

Ordering code

Model: **OP - M T - 0 5 0 4 - T V - 4 6**

Series _____
 Line _____
 Model _____